

ETHERLINE® GUARD

Device for monitoring the cable status

Stationary monitoring device to monitor the service life and performance of a data cables at risk of failure.

Info

compact design



Componentes de automação complementares da LAPP



Engenharia de máquinas e instalações

Vantagens

Increase in system availability through predictable downtimes - reduced maintenance costs.

Easy start-up with automated parameterization ("teach-in" in a few seconds).

Does not require a new data line or changes to the cable design; Retrofitting into the existing network structure is possible at any time.

Reliable IIoT communication thanks to the MQTT interface (for status / data evaluation, settings, WLAN configuration, updates, etc.).

Âmbitos de aplicação

For monitoring the service life of a data cable at risk of failure (e.g. function-critical data cable in dynamic applications).

Suitable for data cables in accordance with the 100BASE-TX transmission standard (up to 100 Mbit/s) according to IEEE 802.3.

Also suitable for EtherCAT, EtherNET/IP and 2-pair PROFINET applications.

For use in the control cabinet (protection class IP 20).

For use in Ethernet-based automation technology networks.

Projeto do produto

Space-saving thanks to its uniquely compact design.

Available in two versions: wired LAN version "PM03T" and wireless WLAN version "PM02TWA".

ETHERLINE® GUARD

Dados técnicos

power supply:	DC 24 V (18-30 V DC)
Tipo de proteção:	IP20
Faixa de temperatura:	-40°C to +65°C

Observação

As imagens e gráficos demonstradas não são reprodução fiel do produto, são meramente ilustrativos
Os preços são preços líquidos sem IVA e sobretaxas. Venda apenas para clientes empresariais.



ETHERLINE® GUARD

Código do Produto	Descrição do Produto
21700151	ETHERLINE GUARD PM02TWA
21700150	ETHERLINE GUARD PM03T

Última atualização (26.04.2024)

©2024 Lapp Group - all rights reserved.

Gestão de Produtos <http://lappbrasil.lappgroup.com>

Você pode encontrar os dados técnicos atuais na folha de dados correspondente.

PN 0456 / 02_03.16